



MULTIBOX

DTT Micro Head End

PRODUCT INFORMATION

Multibox

The Multibox is a unique solution to be able to keep watching TV on all televisions in your home even after the analogue transmissions have been shut down. With the Multibox you can watch all free digital channels on all your televisions.



Features:

- Compact unit with 3 DVB-T receivers
- Watch free-to-air digital programs on all TV-sets
- 3 embedded modulators
- Automatic installation
- NICAM stereo
- 12-volt power supply
- Very low power consumption



DVB's main transmission standards, DVB-S for Satellite, DVB-C for Cable and DVB-T for terrestrial, dominate the world and are the basis for most of the alternative standards.

design for TV

TECHNICAL SPECIFICATION

(This specification may be subject to change without notice).

3 x DVB-T Terrestrial Receiver

Input frequency	470-860 MHz
Connector	Type IEC female, 75 ohm
Input level	32-77 dBuV
Bandwidth	8 MHz

MPEG Decoder - Video

Standard	PAL
Picture aspect ratio	Letterbox, Anamorphic
Teletext	VBI
Subtitling	Teletext or DVB subtitling

Miscellaneous

Power supply	12 VDC (9-16 V)
Power consumption	Typ. 12 W
Dimension	180x190x26 mm (excl. connectors)
Weight	Approx. 660 g
Operating temperature	-20 to +45°C

Modulator

3 modulators	
Modulation standard	PAL
Audio	FM-mono, NICAM stereo
Output channels	4 predefined settings on VHF Pre selected: S11, 231.25 MHz S13, 245.25 MHz S16, 266.25 MHz
Output level	Typ. 80 dBuV, fixed
Lopp through of Digital signals	UHF 470-860 MHz
Built-in aerial amplifier	5 dB
RF output connector	Type IEC male, 75 Ω



To view our full line of Professional E-series Products, visit our Web site at www.a2b.se.



A2B Electronics AB
229100
P.O. Box 14
SE-591 21 Motala
Sweden

Phone +46 141
229100
Fax +46 141 229101
E-mail market@a2b.se
www.a2b.se